

| Date: | Туре: |
|---------------|--------------|
| Project Name: | Part Number: |

LED FLOOD LIGHT













DESCRIPTION

Reno compact flood lights are water resistant rated at IP65. Creating bright, security and spot lighting for a variety of applications such as perimeter, entryway, facades, landscapes, retail and residential complexes and architectural lighting. Can mount in almost any angle with a yoke-style arm and half-inch NPT threaded nipple

FEATURES

- Die-cast aluminum housing with Glass Lens
- (prevent yellowing)
- L70 rated chip for over 100,000 projected life hours
- 1/2" NPT stainless steel threaded nipple
- Dual Voltage 120-347V
- -40°c~ to 50°c operating temperature
- 5 Year Warranty

APPLICATIONS

- Parking Area
- Station
- Warehouse

SPECIFICATION

| ORDER # | MODEL# | WATTS | VOLTAGE(V) | BEAM ANGLE | INITIAL LUMENS | ССТ | CRI |
|---------|-------------------|-------|------------|---------------|-------------------|-------|-----|
| R54001 | RENO-FL-40W-D4-4K | 40W | 120-347V | Т3 | 5250 | 4000K | 74 |
| R54002 | RENO-FL-40W-D4-5K | 40W | 120-347V | Т3 | 5250 | 5000K | 70 |
| R54003 | RENO-FL-60W-D4-4K | 60W | 120-347V | Т3 | 7350 | 4000K | 74 |
| R54004 | RENO-FL-60W-D4-5K | 60W | 120-347V | Т3 | 7350 | 5000K | 70 |

DIMENSION



LUMINOUS EMITTANCE



