

| | |
|---------------|--------------|
| Date: | Type: |
| Project Name: | Part Number: |

LED SLIM POTLIGHT



FEATURES

- IC-rated and Air-Tight ready and may be in direct contact with insulation
- Can be installed in shallow plenum spaces
- Multi CCT Switchable (3000/4000/5000K)
- Flicker-free 120V forward-phase Triac dimming down to 5%
- 277-347V Driver Available
- 50,000 hours lifespan
- 5-year warranty

APPLICATIONS

- Office Lighting
- Commercial Applications
- Damp & Wet location Installation
- Residential

SPECIFICATION

| ORDER # | MODEL# | BEAM ANGLE | LUMENS OUTPUT | HOUR RATING | WATTS | VOLTS | SIZE | CCT | CRI |
|---------|--------------------|------------|---------------|-------------|-------|-------|------|---------------------|-----|
| R36008 | RENO-3-S6W-345KWH | 120° | 400lm | 25,000 | 6W | 120V | 3" | 3000/ 4000/5000K | 80 |
| R36009 | RENO-4-S9W-345KWH | 120° | 600lm | 25,000 | 9W | 120V | 4" | 3000/ 4000/5000K | 80 |
| R36010 | RENO-6-S12W-345KWH | 120° | 800lm | 25,000 | 12W | 120V | 6" | 3000/ 4000/5000K | 80 |
| R36012 | RENO-8-S22W-345KWH | 120° | 1640lm | 25,000 | 22W | 120V | 8" | 3000/ 4000/5000K | 80 |

ACCESSORY INFORMATION

| ORDER # | MODEL# | DESCRIPTION |
|---------|-------------------|--|
| R39105 | LED-HBL015-347V-D | AC277V-347V Driver for slim panel light 4" & 6" non dimmable |
| R39106 | LED-HBL033-347V-D | AC277V-347V Driver for slim panel light 8" non dimmable |
| R39101 | RENO-4-GR | 4" Goof Ring outside Ø 5 3/4" |
| R39102 | RENO-6-GR | 6" Goof Ring outside Ø 8" |
| R39103 | RENO-8-GR | 8" Goof Ring Ø 9 1/2" |

| | |
|---------------|--------------|
| Date: | Type: |
| Project Name: | Part Number: |

DIMENSION

